



JABO SUPPLY CORPORATION

SUCTION & DISCHARGE

JABO CAN ASSEMBLE ANY HOSE IN OUR 9,000 SQ FT HOSE SHOP



SUCTION & DISCHARGE

JABO SUPPLY



5 LOCATIONS

PARKERSBURG, WV

10085 Emerson Avenue 26102
(304) 464-4400

MORGANFIELD, KY

118 Jim Veatch Road, 42437
(270) 389-3430

HUNTINGTON, WV

209 Braley Street, 25705
(304) 736-8333

NORTON, VA

205 Hawthorne Drive, 24273
(276) 679-1224

BEAVER, WV (BECKLEY)

227 C&O Shop Road 25813
(304-252-0000

SINCE 1964 SERVICE IS MORE THAN A PROMISE

SUCTION & DISCHARGE

T202AA SUCTION & DISCHARGE

150 PSI



T202AA Series

150 PSI EPDM

General Purpose

Water S & D Hose

FOR APPLICATIONS INVOLVING
INDUSTRIAL ACID CHEMICALS AND
ALCOHOLS, PLEASE REFER TO T505OG
AND T509OE CHEMICAL HOSES

General Applications:

Suction and discharge of non-corrosive liquids for irrigation, construction, fertilizers and lasso acid solutions.

Construction:

Tube: Black EPDM.

Reinforcement: Spiraled high tensile textile cords with flexible steel helix wire.

Cover: Black EPDM – abrasion and ozone resistant.

Working Pressure:

Constant Pressure – 10 Bar (150 PSI)

Service Temperature Range:

-40°F (-40°C) to +212°F (+100°C)

SUCTION & DISCHARGE

JABO PART#	SIZE	LENGTH	PSI RATING
*	1"	100'	150
*	1-1/4"	100'	150
034-10015	1-1/2"	100'	150
034-10020	2"	100'	150
*	2-1/2"	100'	150
034-10030	3"	100'	150
034-10040	4"	100'	150
*	5"	20'	150
*	5"	50'	150
034-10060	6"	20'	150
*	6"	25'	150
034-10080	8"	20'	150
034-10082	8"	25'	150
*	10"	20'	150
*	12"	20'	150
*Non Stock - Call Jabo Supply			
PRICED BY FOOT			


Nominal Specifications

Series Number	ID (in)	ID (mm)	OD (in)	OD (mm)	Max Rec. WP (psi)	Vacuum HG (in)	Min. Bending Radius at 68°F (in)	Standard Length (ft)	Weight (lbs/ft)
T202AA100	1	25	1.38	35	150	30	4	100	0.47
T202AA125	1 1/4	32	1.65	42	150	30	5	100	0.56
T202AA150	1 1/2	38	1.89	48	150	30	6	100	0.64
T202AA200	2	51	2.40	61	150	30	8	100	0.84
T202AA250	2 1/2	63	2.95	75	150	27	10	100	1.20
T202AA300	3	76	3.46	88	150	27	12	100	1.44
T202AA350	3 1/2	90	4.02	102	150	27	14	100	1.82
T202AA400	4	102	4.49	114	150	27	16	100	2.03
T202AA500	5	127	5.55	141	150	24	25	20/50/100	3.18
T202AA600	6	152	6.54	166	150	24	30	20/25/50/100	4.01
T202AA800	8	203	8.70	221	150	21	40	20/25	6.59
T202AA1000	10	254	10.71	272	150	18	50	20	9.03
T202AA1200	12	305	12.87	327	150	18	61	20	12.54

SUCTION & DISCHARGE

SUCTION & DISCHARGE

T223AA SUCTION & DISCHARGE

300PSI			
			
JABO PART#	SIZE	LENGTH	PSI RATING
*	2"	100'	300
*	2-1/2"	100'	300
034-10031	3"	100'	300
034-10041	4"	100'	300
034-10061	6"	100'	300
*	8"	40'	300
<i>*Non Stock - Call Jabo Supply</i>			
300 PSI EPDM Heavy Duty S&D Hose			
PRICED BY FOOT			

Working Pressure:

Constant Pressure – 20 Bar (300 PSI)

Service Temperature Range:

-22°F (-30°C) to 176°F (+80°C)

T223AA

300 PSI EPDM

Heavy Duty S & D Hose

FOR APPLICATIONS INVOLVING
INDUSTRIAL ACID CHEMICALS AND
ALCOHOLS, PLEASE REFER TO T505OG
AND T509OE CHEMICAL HOSES

General Applications:

Heavy duty water suction and discharge applications for irrigation, agriculture, mining and construction. Designed for long service life in heavy duty applications for water suction and delivery service.

Construction:**Tube:** Black conductive EPDM.**Reinforcement:** Spiraled high tensile textile cords with flexible steel helix wire.**Cover:** Black conductive EPDM – abrasion and ozone resistant.**Nominal Specifications**

Series Number	ID (in)	ID (mm)	OD (in)	OD (mm)	Max Rec. WP (psi)	Vacuum HG (in)	Min. Bending Radius at 68°F (in)	Standard Length (ft)	Weight (lbs/ft)
T223AA200	2	51	2.48	63	300	30	8	100	0.955
T223AA250	2 1/2	63	3.03	77	300	27	10	100	1.395
T223AA300	3	76	3.54	90	300	27	12	100	1.715
T223AA400	4	102	4.57	116	300	27	16	100	2.350
T223AA600	6	152	6.61	168	300	24	24	100	4.580
T223AA800	8	203	8.86	225	300	21	32	40	7.335

MOST COMMONLY USED HOSE ENDS

SUCTION & DISCHARGE

CAMLOCKS

MALE CAM X HOSE BARB



FEMALE CAM X HOSE BARB



Available in Zinc, SS, Polypropylene

PIPE THREADS

KING NIPPLE X HOSE BARB



Available in Zinc & SS

VICTAULIC



Available in 316 SS, Galvanized

FLANGES

FLOATING FLANGE



FIXED FLANGE



Available in Carbon Steel, SS 304, SS 316

CHICAGO STYLE COUPLING



Available in Zinc

FABRICATION



